

# RF AMPLIFIER

## MODEL *TM3006*

Available as: TM3006, 4 Pin TO-8 (T4)  
 TN3006, 4 Pin Surface Mount (SM3)  
 BX3006, Connectorized Housing (H1)

### Features

- High Gain: 30 dB Typical
- Low VSWR: 1.3:1 Typical
- Operating Temp. - 55 °C to + 85 °C
- Environmental Screening Available

### Specifications

CHARACTERISTIC	TYPICAL Ta= 25 °C	MIN/MAX Ta = -55 °C to +85 °C
Frequency	100 - 200 MHz	100 - 200 MHz
Gain (dB)	30	29 Min.
Power @ 1 dB Comp. (dBm)	+18	+17 Min.
Reverse Isolation (dB)	-35	-33 Max.
VSWR In	1.3:1	1.5:1 Max.
Out	1.3:1	1.5:1 Max.
Noise Figure (dB)	3.0	3.5 Max.
Power Vdc	+12	+12
mA	72	75 Max.

Note: Care should always be taken to effectively ground the case of each unit.


### Typical Intermodulation Performance at 25 ° C

Second Order Harmonic Intercept Point ..... +54 dBm (Typ.)  
 Second Order Two Tone Intercept Point ..... +48 dBm (Typ.)  
 Third Order Two Tone Intercept Point ..... +31 dBm (Typ.)

### Maximum Ratings

Ambient Operating Temperature ..... -55°C to + 100 °C  
 Storage Temperature ..... -62°C to + 125 °C  
 Case Temperature ..... + 125 °C  
 DC Voltage ..... + 18 Volts  
 Continuous RF Input Power ..... + 13 dBm  
 Short Term RF Input Power ..... 50 Milliwatts (1 Minute Max.)  
 Maximum Peak Power ..... 0.5 Watt (3 µsec Max.)

### Typical Performance Data



Legend ——— + 25 °C    - - - + 85 °C    ····· -55 °C



Spectrum Microwave · 2144 Franklin Drive N.E. · Palm Bay, Florida 32905 · PH (888) 553-7531 · Fax (888) 553-7532 05/10/04

www.spectrummicrowave.com Spectrum Microwave (Europe) · 2707 Black Lake Place · Philadelphia, Pa. 19154 · PH (215) 464-4000 · Fax (215) 464-4001