

RF AMPLIFIER

MODEL *TM5147*

Available as: TM5147, 4 Pin TO-8 (T4)
 TN5147, 4 Pin Surface Mount (SM3)
 FP5147, 4 Pin Flatpack (FP4)
 BX5147, Connectorized Housing (H1)

Features

- Low Noise Figure: <3.5 dB Typical
- Wide Frequency Range
- Operating Temp. - 55 °C to +85 °C
- Environmental Screening Available

Specifications

CHARACTERISTIC	TYPICAL Ta= 25 °C	MIN/MAX Ta = -55 °C to +85 °C
Frequency	20-1100 MHz	20-1100 MHz
Gain (dB)	14	13.0 Min.
Power @ 1 dB Comp. (dBm)	+11	+9.0 Min.
Reverse Isolation (dB)	-18	-16 Max.
VSWR In	<1.6:1	2.0:1 Max.
Out	<1.6:1	2.0:1 Max.
Noise Figure (dB)	<3.5	4.0 Max.
Power Vdc	+15	+15 Min.
mA	27	29 Max.

Note: Care should always be taken to effectively ground the case of each unit.


Typical Intermodulation Performance at 25 ° C

Second Order Harmonic Intercept Point.....+39 dBm (Typ.)
 Second Order Two Tone Intercept Point.....+33 dBm (Typ.)
 Third Order Two Tone Intercept Point..... +23 dBm (Typ.)

Maximum Ratings

Ambient Operating Temperature -55°C to + 100 °C
 Storage Temperature -62°C to + 125 °C
 Case Temperature + 125 °C
 DC Voltage + 18 Volts
 Continuous RF Input Power + 13 dBm
 Short Term RF Input Power 50 Milliwatts (1 Minute Max.)
 Maximum Peak Power 0.2 Watt (3 μsec Max.)

Typical Performance Data



Legend ——— + 25 °C - - - - + 85 °C · · · · · -55 °C

Linear S-Parameters

FREQ. MHz	---- S11 ----		---- S21 ----		---- S12 ----		---- S22 ----	
	Mag	Deg	Mag	Deg	Mag	Deg	Mag	Deg
10	.22	-155	4.96	-173	.12	8	.25	164
50	.22	-179	5.06	176	.12	3	.22	164
100	.22	175	5.06	169	.12	2	.21	155
250	.21	158	5.06	150	.12	1	.22	128
500	.18	135	5.04	121	.14	- 0	.23	82
750	.13	117	5.12	91	.15	- 6	.24	42
1000	.08	121	5.21	59	.16	-14	.21	6
1250	.10	153	5.16	23	.17	-21	.17	- 26
1500	.16	146	4.70	- 17	.18	-29	.11	- 40



Spectrum Microwave · 2144 Franklin Drive N.E. · Palm Bay, Florida 32905 · PH (888) 553-7531 · Fax (888) 553-7532 6/18/04

www.spectrummicrowave.com Spectrum Microwave (Europe) · 2707 Black Lake Place · Philadelphia, Pa. 19154 · PH (215) 464-4000 · Fax (215) 464-4001