

# RF AMPLIFIER

## MODEL *TM6659*

Available as: TM6659, 4 Pin TO-8 (T4)  
 TN6659, 4 Pin Surface Mount (SM3)  
 FP6659, 4 Pin Flatpack (FP4)  
 BX6659, Connectorized Housing (H1)

### Features

- High Output Power: +22 dBm Typical
- High Third Order Intercept: +36 dBm Typical
- Operating Temp. - 55 °C to +85 °C
- Environmental Screening Available

### Specifications

CHARACTERISTIC	TYPICAL Ta= 25 °C	MIN/MAX Ta = -55 °C to +85 °C
Frequency	5 - 800 MHz	10 - 700 MHz
Gain (dB)	10.5	9.0 Min.
Power @ 1 dB Comp. (dBm)	+22	+20 Min.
Reverse Isolation (dB)	-14	-13 Max.
VSWR In	<1.75:1	2.0:1 Max.
Out	<1.5:1	2.0:1 Max.
Noise figure (dB)	6.5	8.0 Max.
Power Vdc	+15	+15
mA	88	95 Max.

Note: Care should always be taken to effectively ground the case of each unit.


### Typical Intermodulation Performance at 25 ° C

Second Order Harmonic Intercept Point ..... +52 dBm (Typ.)  
 Second Order Two Tone Intercept Point ..... +46 dBm (Typ.)  
 Third Order Two Tone Intercept Point ..... +36 dBm (Typ.)

### Maximum Ratings

Ambient Operating Temperature ..... -55°C to + 100 °C  
 Storage Temperature ..... -62°C to + 125 °C  
 Case Temperature ..... + 125 °C  
 DC Voltage ..... + 18 Volts  
 Continuous RF Input Power ..... + 18 dBm  
 Short Term RF Input Power ..... 50 Milliwatts (1 Minute Max.)  
 Maximum Peak Power ..... 0.5 Watt (3 µsec Max.)

### Typical Performance Data



Legend ——— + 25 °C    - - - - + 85 °C    ······ -55 °C

### Linear S-Parameters

FREQ. MHz	S11		S21		S12		S22	
	Mag	Deg	Mag	Deg	Mag	Deg	Mag	Deg
5	.21	-131	3.33	-165	.15	11	.21	161
50	.17	162	3.41	170	.15	- 1	.17	159
100	.18	139	3.38	158	.16	- 0	.16	145
200	.20	103	3.34	136	.17	- 4	.13	112
300	.23	74	3.32	115	.18	- 9	.11	69
400	.24	51	3.34	94	.19	-16	.10	18
500	.23	30	3.36	72	.19	-23	.12	- 33
600	.20	6	3.41	49	.20	-31	.18	- 74
700	.13	- 25	3.40	25	.19	-39	.23	-105
800	.05	-103	3.31	- 1	.19	-46	.28	-135



Spectrum Microwave · 2144 Franklin Drive N.E. · Palm Bay, Florida 32905 · PH (888) 553-7531 · Fax (888) 553-7532 2/26/04

www.spectrummicrowave.com Spectrum Microwave (Europe) · 2707 Black Lake Place · Philadelphia, Pa. 19154 · PH (215) 464-4000 · Fax (215) 464-4001