Voltage Controlled Oscillator

Model HV27T-11
Model HV27SM-112

RF Band — 100 to 200 MHz

Electrical Specifications:[1]

Parameter	Specifications
Frequency Range	100 to 200 MHz
Power Output at 25°C (50 Ohm load)	+10 dBm, min.
Power Output Variation vs. Temperature	1.0 dB, typical
Frequency Drift vs. Temperature [2]	4 MHz, typical
Frequency Pulling (12 dB Return Loss)	5 MHz, typical
Frequency Pushing	0.5 MHz/V, typical
Tuning Voltage Limits	0 to +20 VDC
SSB Phase Noise (50 kHz offset)	-125 dBc/Hz, typical
Harmonics [3]	-12 dBc, typical
Spurious	-70 dBc, max.
Bias Voltage [4]	+15 VDC ±1%
Bias Current [5]	25 mA, typical
Operating Temperature	-55 to +100°C

Notes:

1. Specifications guaranteed over the operating temperature range. Those specifications indicated as typical are not guaranteed. Plots exemplify typical performance at +25°C
2. Total frequency drift over the full temperature range.
3. Worst case harmonics over the frequency range.
4. Alternate bias voltages available.
5. Lower bias current available.
6. Military screening available.

HV27T-11

Outline: TO-8



All dimensions are in inches and [mm].

HV27SM-112

Outline: SMV2



Typical Performance at 25°C







Spectrum Microwave · 2144 Franklin Drive N.E. · Palm Bay, FL 32905 · PH (888) 553-7531 · Fax (888) 553-7532

www.SpectrumMicrowave.com Spectrum Microwave (Europe) · 2707 Black Lake Place · Philadelphia, PA 19154 · PH (215) 464-4000 · Fax (215) 464-4001